



# Safety Data Sheet

# Precoat Supa DS

Hazardous Substance and Non Dangerous Goods

## 1: IDENTIFICATION OF MATERIAL AND SUPPLY COMPANY

**Supplier:** Bituminous Products Pty Ltd  
33 Violet Street  
REVESBY NSW 2212

ABN No: 19 106 887 094  
Business Phone: 02 9772 4433  
Facsimile: 02 9792 1016

**EMERGENCY CONTACT:** John Arvanitidis (Phone) 02 9772 4433  
(A/H) 0417 927 715

**PRODUCT NAME:** Precoat Supa DS  
**UN No.:** None  
**DESCRIPTION:** (Proper Shipping Name) none  
**DANGEROUS GOODS CLASS:** Not Dangerous Goods  
**PACKAGING GROUP:** None  
**HAZCHEM:** Not applicable  
**POISONS SCHEDULE:** S6  
**MANUFACTURER'S PRODUCT CODE:** 220-3005  
**RECOMMENDED USE:** Coating of aggregate for spray sealing

## 2: HAZARDS IDENTIFICATION

**HAZARD CLASSIFICATION:** Classified as hazardous according to Safe Work Australia  
Not classified as Dangerous Goods according to the Australian Dangerous Goods Code

**Pictogram**  
None required

**Signal Word**  
Warning

**GHS Hazard Classification**  
Flammable Liquids – Category 4

**Hazard Statement(s)**  
H227 Combustible liquid



### Prevention Precautionary Statement(s)

- P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P210 Keep away from all sources of ignition – No smoking  
P280 Wear protective clothing, gloves, eye/face protection and suitable respirator.

### Response Precautionary Statement(s)

- P101 If medical advice is needed, have product container or label at hand.  
P303+P361+P353 If ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P308+ P313 If exposed or concerned: Call POISON CENTER/ doctor  
P370+P378 In case of fire: Use alcohol resistant foam, standard foam or dry agent or water fog for extinguishing.

### Storage Precautionary Statement(s)

- P403+P233 Store in a well ventilated place. Keep container tightly closed.

### Disposal Precautionary Statement(s)

- P501 Dispose of container in accordance with regional and national regulations.

### Dangerous Goods Classification

Not Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code for the Transport of Dangerous Goods by Road & Rail.

**Class:** Not Applicable Combustible Liquid C2

## 3: COMPOSITION INFORMATION

<u>CHEMICAL ENTITY</u>	<u>CAS NUMBER</u>	<u>PROPORTION</u>
BITUMEN	(8052-42-4)	20 - < 50 %
DIESEL	(68334-30-5)	20 - < 50 %
AMINES	(61791-14-8)	0.5 - < 5%

## 4: First Aid Measures

If poisoning occurs seek medical assistance or contact:

**Product Name: PRECOAT SUPA DS**

**Page 2 of 8**



## Poisons Information Centre on 131 126

**INGESTION/SWALLOWED:** Do not induce vomiting. Rinse mouth with water. Give a glass of water to drink. If vomiting occurs give further water to drink. SEEK MEDICAL ASSISTANCE.

**EYE CONTACT:** Flush thoroughly with water for at least 15 minutes. SEEK MEDICAL ADVICE.

**SKIN CONTACT:** For large scale contamination, drench with water and remove contaminated clothing. Wash skin and hair thoroughly with soap and water. If blistering occurs, cover with a clean bandage and SEEK MEDICAL ASSISTANCE.

**INHALATION:** Remove casualty to fresh air and keep at rest until recovered. If not breathing, apply artificial respiration. If in cardiac arrest, apply external cardiac massage. SEEK MEDICAL ASSISTANCE.

**PPE for FIRST AIDERS:** Overalls, safety glasses, PVC or Nitrile gloves. If exposed to vapours, use respirator with organic vapour filter.

**ADVICE TO DOCTOR:** Product may be removed from skin using cotton wool pads soaked in castor oil or hand cleaner. Treatment should be directed toward control of symptoms and conditions.

### 5: Fire Fighting Measures

**HAZCHEM CODE:** Not Applicable

**FIRE EXTINGUISHING MEDIA:** Dry chemical, foam, carbon dioxide, and water fog.

**SPECIFIC HAZARDS:** Combustible Liquid at elevated temperatures can form flammable vapour mixtures with air. Avoid ignition sources. No smoking.

**FIRE AND EXPLOSION HAZARD:** Closed containers may explode when exposed to heat (fire). Keep containers cool with water spray. This product will emit flammable vapours. Will produce toxic fumes when burning – wear breathing apparatus.



## 6: Accidental Release Measures

**SMALL SPILLS:** Wear safety glasses, impermeable gloves and organic vapour respirator if required. Clean up with rags or paper towels. Allow to dry in well ventilated area and dispose of with dray waste.

**LARGE SPILLS:** Stop source of leak/loss of containment if safe to do so. Isolate and eliminate ignition sources. Remove all non - essential personnel from area. Clean up personnel to wear boots overalls, solvent proof gloves, goggles or face visor and organic vapour respirator. Work upwind and/or provide intrinsically safe ventilation. Prevent contamination of drains and waterways. Use absorbent to clean up spilt material using non sparking tools. Collect spent absorbent material in sealed drums or containers and dispose of according to local environmental authority requirements. Seek assistance of EPA and emergency services if there is a chance of entering drains and water ways.

## 7: Handling and Storage

**DANGEROUS GOODS CLASS:** None      **SUB RISK:** None

**Handling:** Avoid skin contact and inhalation of vapour and mist. Do not use pressure to empty drums.

**Storage:** Store in a cool dry place. Store in areas/building designed to comply with the appropriate dangerous goods regulations for combustible liquids. Protect from physical damage. Keep container closed when not in use.

**Transport:** should be in accordance with the Australian Dangerous Goods Code for the transport of dangerous goods by road and rail for combustible liquids.

## 8: Exposure Controls, Personal Protection

**National Exposure Standards:** There is no Australian Workplace Standard for this product. However, TWA for Bitumen is 5 mg/m<sup>3</sup> and Oil Mist is 5 mg/m<sup>3</sup> according to Safe Work Australia.

TWA is **Time Weighted Average** airborne concentration over an eight hour period five days per week over an entire working life.

Provide adequate ventilation. If using indoors, keep windows and doors open during use. Keep containers closed when not in use. These directions should prevent the TWA being exceeded.



**Biological Limit Values:** No Biological Limit Value allocated as per the National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia).

**ENGINEERING CONTROLS:** Keep containers closed when not in use. Ensure ventilation is adequate to maintain air concentrations below exposure standards. Use only in well ventilated areas. If ventilation cannot be provided, wear organic vapour respirator. Do not enter confined spaces where vapours may have accumulated.

**PERSONAL PROTECTION EQUIPMENT:** OVERALLS, SAFETY SHOES OR BOOTS, SAFETY GLASSES, GLOVES, RESPIRATOR.

A respirator suitable for organic vapours must be used in poorly ventilated areas. Air supplied respirators should be used in areas with inadequate oxygen and high vapour concentrations.

**Glove type** - PVC gloves or other solvent proof gloves should be used when handling material.

**Eye protection** - Use close fitting chemical safety goggles, otherwise use safety glasses fitted with side shields. If splashing is possible use a face shield over safety glasses as added protection.

**Clothing protection** – Wear industrial-type work clothing or overalls and safety footwear.

**Workplace-** Ensure that eyewash and safety shower are available and in good working condition wherever this product is being used or manufactured.

**Hygiene measures:** Keep away from food and drink. Do not eat or drink while using this product. Always wash hands thoroughly prior to eating, drinking or using the toilet. Always launder or replace contaminated clothing or PPE before storing or reusing.

## 9: Physical and Chemical Properties

<b>FORM:</b>	Liquid
<b>APPEARANCE:</b>	Black liquid
<b>ODOUR:</b>	Mineral Oil Bitumen characteristic
<b>PACK SIZE(S):</b>	Bulk
<b>BOILING POINT (°C):</b>	> 300° C
<b>MELTING POINT (°C):</b>	Not Applicable
<b>VAPOUR PRESSURE (KPa) :</b>	Not Applicable
<b>SPECIFIC GRAVITY @ 25 °C:</b>	0.91
<b>SOLUBILITY IN WATER (% BY WT.):</b>	Not soluble
<b>FLASH POINT (°C)-METHOD:</b>	>65 ° C (closed cup)





**Bioaccumulative potential:** No information is available.

**Mobility:** No information is available.

### 13: Disposal Considerations

#### Disposal Methods:

Wherever possible, re-use, reprocess or recycle any reclaimed material to reduce waste.

- Contained spills need to be soaked up and disposed into a metal container (avoid using plastic containers).
  - Once dry, the absorbed material may be disposed of as solid waste in conformity with the requirements of the Regulatory Authorities.
  - Refer Section 8 for Exposure Controls

### 14: Transport Information

**Road and Rail Transport:** Not Classified as Dangerous Goods by the Australian Dangerous Goods Code for Transport by Road and Rail

Classified as a combustible liquid by the Australian Dangerous Goods Code for Transport by Road and Rail

Classified as Flammable Liquid Category 4 GHS Classification Safe Work Australia

**U.N. Number:** None

**Proper Shipping Name:** Not Applicable

**DG Class:** None

**Packing Group:** None

**Hazchem Code:** None

**Emergency Response Guide No 15**

**Segregation:** Not Applicable

**Marine Transport:** Not Classified as Dangerous Goods by the International Maritime Dangerous Goods Code (IMDG Code) for Transport by Sea.

**Air Transport:** Not Classified as Dangerous Goods by the International Air Transport Association (IATA). Dangerous Goods Regulations for transport by air.

### 15: Regulatory Information

**This material is not subject to the following international agreements:**

Montreal Protocol (Ozone depleting substances)

**Product Name:** PRECOAT SUPA DS

**Page 7 of 8**



The Stockholm Convention (Persistent Organic Pollutants)  
The Rotterdam Convention (Prior Informed Consent)

**This material is subject to the following requirements:**

**Australian Dangerous Goods Code, IMDG, IATA**

**Class:** None

**U.N. Number:** None

**Proper Shipping Name:** None

**The Standard for the Uniform Scheduling of Medicines and Poisons**

**(SUSMP) Therapeutic Goods Act (Commonwealth)**

**Poisons Schedule:** S6

**Storage:**

AS1940 APPLIES WHEN STORED IN BULK QUANTITIES

**16: Other Information**

**Contact Person:** **John Arvanitidis**, Bituminous Products Pty Ltd  
02 9772 4433  
After hours 0417 927 715

This Safety Data Sheet has been compiled in accordance with GHS Guidance for the preparation of Safety Data Sheets and COP Preparation of SDS for Hazardous Chemicals Safe Work Australia.

Where applicable, specific chemical composition details are provided to allow the product to be classified according to UN Number, HAZCHEM coding etc.

The information contained herein is based on the data available to BITUMINOUS PRODUCTS PTY LTD from both our suppliers and technical sources and from recognized published references and is believed to be both accurate and reliable. BITUMINOUS PRODUCTS PTY LTD has made no effort to censor or to conceal deleterious aspects of this product. Since we cannot anticipate or control the many different conditions under which this information and our products may be used, each user should review these recommendations in the specific context of the intended application and confirm whether they are appropriate.

Due care should be taken to make sure that the use or disposal of the product is in compliance with the appropriate Federal, State, and Local Government regulations.

**END OF SDS**