



Primers & Sealants

bitumen based products

BITULASTIC HOT POUR PRIMER



Description

BITULASTIC Hot Pour Primer is an adhesive highly rubberised bitumen based primer, formulated to adhere to dry surfaces to provide a fusion bond for hot applied BITUFLEX crack sealant.

Uses

Priming of concrete joints or cracks prior to sealing with hot applied joint sealant.

SURFACE PREPARATION

All surfaces to be primed must be clean and dry and free from oils, waxes and greases.

APPLICATION

Can be applied by brush, spray, roller, broom or squeegee.

SPECIFICATION

| | |
|--------------------------|------------------------------|
| COLOUR: | Straw Colour |
| VISCOSITY: | 100 sec Ford Cup No 4 @ 25°C |
| COVERAGE: | 8 sq. m /litre |
| DRYING TIME: | 10 to 15 minutes touch dry. |
| SOLIDS CONTENT: | 50% ± 5% w/w |
| SPECIFIC GRAVITY: | 0.896 |
| PACKAGING: | 20 Litre Drums |

Steel containers are recyclable provided they are empty and any residual product is dry.

Safety

Refer to Safety Data sheets before use.

Eliminate all potential ignition sources during application.

Avoid breathing vapours.

Avoid contact with skin.

Always wear appropriate PPE.

DO NOT allow product or washings to enter stormwater or sewer systems.

BITUMINOUS PRODUCTS

Sydney
(02)9772 4433

Brisbane
(07)3260 1088

Melbourne
(03)9706 6444

Townsville
(07)4774 8311

Perth
0401 564 511