

BITUNAMEL PRIMER

an Industrial Bitumen based primer for water proofing



Bitunamel primer is an Industrial Bitumen base paint formulated to adhere to masonry and metal surfaces to improve adhesion with torch on membranes

USES:

Concrete roofing prior to torch on membrane
All metal surfaces for corrosion protection.
All bituminous surfaces for moisture protection.
Concrete joints prior to sealing with joint sealant.

SURFACE PREPARATION

All surfaces to be painted must be clean and dry and free from oils, waxes and greases. New hot dip galvanizing must be weathered 6 months before application of any paint.

APPLICATION:

Can be applied by brush, spray, roller, broom or squeegee. Where sunlight (UV) exposure is encountered we recommend overcoating with BITUNAMEL SILVER.

SPECIFICATION AND TECHNICAL DATA

COLOUR: Black
VISCOSITY: 50 sec \pm 5 sec Ford Cup No 4 @ 25°C
COVERAGE: Painting – 3m sq./litre in a two coat application.
Priming – 10m sq./litre
DRYING TIME: 15 to 20 minutes (touch dry)
SOIDS CONTENT: 50% \pm 5% w/w
SPECIFIC GRAVITY: 0.92

PACKAGING: 20 Litre and 205 Litre Drums
Steel containers are recyclable provided they are empty and any residual product is dry.

Safety

Refer to Safety Data sheets before use.
Eliminate all potential ignition sources during application.
Avoid breathing vapours.
Avoid contact with skin.
Always wear appropriate PPE.
DO NOT allow product or washings to enter stormwater or sewer systems.

BITUMINOUS PRODUCTS

Sydney
(02)9772 4433

Brisbane
(07)3260 1088

Melbourne
(03)9706 6444

Townsville
(07)4774 8311

Perth
0401 564 511