

BITUNAMEL T245

Fast drying high solids Industrial Bitumen based paint



DESCRIPTION

Bitunamel T260 primer is a very fast dry, medium solids Industrial Bitumen based paint suitable for all general purpose applications where quick drying is required.

USES: All metal surfaces for corrosion protection.
All masonry and bituminous surfaces for moisture protection.

SURFACE PREPARATION

All surfaces to be painted must be clean and dry and free from oils, waxes and greases. New hot dip galvanizing must be weathered 6 months before application of any paint.

APPLICATION: Can be applied by brush, spray, roller, broom or squeegee. Where sunlight (UV) exposure is encountered we recommend overcoating with BITUNAMEL SILVER.

SPECIFICATION AND TECHNICAL DATA

COLOUR: Black
VISCOSITY: 150 sec \pm 5 sec Ford Cup No 4 @ 25°C
COVERAGE: Painting – 3m sq./litre in a two-coat application.
 Priming – 10m sq./litre
DRYING TIME: 15 to 20 minutes (touch dry)
SOLIDS CONTENT: 80% \pm 5% w/w
SPECIFIC GRAVITY: 0.96

PACKAGING: 205 Litre Drums

Steel containers are recyclable provided they are empty and any residual product is dry.

BITUMINOUS PRODUCTS

Sydney
(02)9772 4433

Brisbane
(07)3260 1088

Melbourne
(03)9706 6444

Townsville
(07)4774 8311

Perth
0401 564 511