

Primers & Sealants

bitumen based products

BLACKJACK SILVER

low viscosity bitumen based aluminum paint (Sprayable)

FLAMMABLE 3

DESCRIPTION:

A low viscosity bitumen based aluminum paint that is UV resistant. Provides a protective barrier for all bitumen-based coatings that are exposed to sunlight. Also provides a bleed through barrier when painting over bitumen based coatings.

USES:

All steelwork, galvanized roofs, potable (drinking) water tanks, all bituminous membranes and coatings.

TECHNICAL DATA:

COVERAGE: 7-10 m2/Litre.

FLASH POINT: 40° C.

DRYING TIME: 6-24 hours. Depending on ambient temperatures.

SPECIFIC GRAVITY: 0.98

THINNERS: Mineral Turps or White Spirits.

APPLICATION

Clean surface free from rust, grease, oil, wax or dirt. Leave new hot dip galvanized iron a minimum of 6 months to weather before coating.

Stir can well before use and apply by brush, roller, or spray. Use spray for best results.

PACKAGING: 1 litre and 4 litre lithographed cans

15 Litre Pails

Steel containers are recyclable provided they are empty and any residual product is dry.

Safety

Refer to Safety Data sheets before use.

Eliminate all potential ignition sources during application.

Avoid breathing vapours.

Avoid contact with skin.

Always wear appropriate PPE.

DO NOT allow product or washings to enter stormwater or sewer systems.

BITUMINOUS PRODUCTS

 Sydney
 Brisbane
 Melbourne
 Townsville
 Perth

 (02)9772 4433
 (07)3260 1088
 (03)9706 6444
 (07)4774 8311
 0401 564 511